

SPECIFICATION OF CABLE GLANDS (MULTIPLE HOLES)

Material

PA 66 (Polyamide)

Fire Behaviour

According to UL 94V-2

Thread

PG, Metric

Temperature

-40°C to +100°C

Colour

Black, Grey

Protection

IP 68

Features

Salt Water Resistant

Weak Acid Resistant

Oil & Grease Resistant

High Sealing Performance

The claws and seals are of excellent design, can hold cable firmly and have a wider cable range



DETAILED DATA OF MULTIPLE HOLES CABLE GLANDS

THREAD	ITEM NO.	CABLE RANGE Φ(mm)	THREAD O.D. C1(mm)	THREAD LENGTH C2(mm)	SPANNER SIZE A&F(mm)
PG 7	MHPG7A-H2-3	1.2-3	12.5	8.5	17/19
	MHPG7A-H3-2.6	1.2-2.6			
	MHPG7A-H4-2.3	1-2.3			
PG 9	MHPG9A-H2-3	1.2-3	15.2	8.5	22/19
	MHPG9A-H3-2.6	1.2-2.6			
	MHPG9A-H4-2.3	1-2.3			
PG 11	MHPG11A -H2-4	1.6-4	18.6	10	24/22
	MHPG11A -H3-4	1.6-4			
	MHPG11A -H4-3.2	1.5-3.2			
	MHPG11A -H6-2.1	1.4-2.1			
PG 13.5	MHPG13.5A -H2-5.3	1.5-5.3	20.4	10	27/24
	MHPG13.5A -H3-5	2-5			
	MHPG13.5A -H4-4	2-4			
PG 16	MHPG16A-H2-6	2.5-6	22.5	10.8	30/27
	MHPG16A-H3-5	2-5			
	MHPG16A-H4-4.5	2-4.5			
PG 21	MHPG21A-H2-8	4-8	28.3	12	36/33
	MHPG21A-H3-8	4-8			
	MHPG21A-H4-7	3.5-7			
	MHPG21A-H5-6	3-6			
	MHPG21A-H6-5.3	2.4-5.3			

PG 29	MHPG29A-H2-10	5-10	37	15	46/41
	MHPG29A-H3-10	5-10			
	MHPG29A-H4-9	4.5-9			
	MHPG29A-H5-8	4-8			
	MHPG29A-H6-7	3.5-7			
PG 36	MHPG36A-H4-12	10-12	47	15	57/50

M12 x 1.5	MHG12A-H2-3	1.2-3	12	8.5	18/19
	MHG12A-H3-2.6	1.2-2.6			
	MHG12A-H4-2.3	1.2-3			
M16 x 1.5	MHG16A-H2-4	1.6-4	16	15	22/22
	MHG16A-H3-4	1.6-4			
	MHG16A-H4-3.2	1.5-3.2			
	MHG16A-H6-2.1	1.4-2.1			
M20 x 1.5	MHG20A-H2-6	2.5-6	20	15	27/27
	MHG20A-H3-5	2-5			
	MHG20A-H4-4.5	2-4.5			
M25 x 1.5	MHG25A-H2-8	4-8	25	15	33/33
	MHG25A-H3-8	4-8			
	MHG25A-H4-7	3.5-7			
	MHG25A-H5-6	3-6			
	MHG25A-H6-5.3	2.4-5.3			
M32 x 1.5	MHG32A-H2-10	5-10	32	15	41/41
	MHG32A-H3-10	5-10			
	MHG32A-H4-9	4.5-9			
	MHG32A-H5-8	4-8			
	MHG32A-H6-7	3.5-7			
M40 x 1.5	MHG40A-H4-12	10-12	40	20	50/50
M63 x 1.5	MHG63A-H3-13	10-13	63	25	75/78

