

SPECIFICATION OF SCREW PLUGS

Material

PA 66 (Polyamide)

Fire Behaviour

According to UL 94V-2

Thread

PG, Metric

Protection

IP 68

Temperature

-40°C to +100°C

Colour

Black, Grey

Features

Dust Proof

Include O Ring.



DETAILED DATA OF SCREW PLUGS (PG)

THREAD	ITEM NO.	AG (mm)	GL (mm)	D (mm)
PG-7	MSP-7	12.5	9.5	16.5
PG-9	MSP-9	15.2	9.5	19.2
PG-11	MSP-11	18.6	10	22.6
PG-13.5	MSP-13.5	20.4	10	24.4
PG-16	MSP-16	22.5	10	26.5
PG-21	MSP-21	24	11	30
PG-29	MSP-29	28.3	11	34
PG-36	MSP-36	37	12	43
PG-42	MSP-42	47	12	53
PG-48	MSP-48	54	12	60

DETAILED DATA OF SCREW PLUGS (METRIC)

THREAD	ITEM NO.	AG (mm)	GL (mm)	D (mm)
M12x1.5	MSP-M12	12	9.5	16
M16x1.5	MSP-M16	16	10	20
M18x1.5	MSP-M18	18	11	22
M20x1.5	MSP-M20	20	11	24
M25x1.5	MSP-M25	25	11	29
M32x1.5	MSP-M32	32	11	38
M40x1.5	MSP-M40	40	12	46
M50x1.5	MSP-M50	50	12	56
M63x1.5	MSP-M63	63	12	69